Bolle Wall 04

BTWA04



MATERIALS

Hand-blown transparent borosilicate glass and hand-finished or electroplated brass WEIGHT INCL. CANOPY

Max 4.5 lbs

POWER INPUT

110-120V 50-60Hz

LIGHT SOURCE (INCLUDED)

ProprietarySoftspot50 LED, 9W, 380 Lumens, 2700K warm white. CRI>95. 50% downwards and 50% upwards.




BOLLE WALL 04

CONFIGURATION

VERSION SIZE (UNIT: IN)

Bolle Wall 04

BTWA04



STEP 1: METAL FINISHES (INCLUDED IN STARTING PRICE)

Brushed Brass	Brushed Bronze	Blackened Brass	Brushed Nickel
BR	BZ	BK	NK

STEP 2: GLASS COLOUR



Transparent **TR**



Iridescent IR



Blushed Gold **BO**



Blushed Sand **SD**



Blushed Peach PC



Blushed Light GreenBlushed Light Blue LG LB



Blushed Smokey Grey **BG**

STEP 3: CANOPY				
Type of Canopy		FINISH	CODE WITH DIMMABLE STANDARD	
			Phasecut	0-10Volt Alternative dimming standard, if required by electrician
	1 Canopy: Ø5×H2 in Driver position: Built-in	Brushed Brass Brushed Bronze Blackened Brass Brushed Nickel	BR120BP BZ120BP BK120BP NK120BP	BR120BV BZ120BV BK120BV NK120BV

Custom colours (RAL Classic): availability and price upon request

Brass Finish

BRUSHED BRASS

Brass hand-finished with horizontal brushing. Protected with a semi-gloss transparent coating.

BRUSHED BRONZE

Brass with accelerated aging to become a bronze finish. Hand-finished with horizontal brushing. Protected with a semi-matt transparent coating.

BLACKENED BRASS

Brass with accelerated aging to become an extra dark chocolate finish. Hand-finished with horizontal brushing. Protected with a semi-matt transparent coating.







BRUSHED NICKEL

Electroplated nickel over Brass with horizontal brushing. Electroplated Nickel over polished brass. Protected with a semi-gloss transparent coating.

POLISHED NICKEL

Protected with a semi-gloss transparent coating.



