



Finishes / bronze



Black patinated bronze

Brown patinated bronze

Gold patinated bronze

Finishes / alabaster



The images above show the standard variations.

GARDE

AURA BRONZE 18 SCONCE


A family of sconces composed of a sand-cast bronze shell and an alabaster disk. Can also be used as a flush mount. Available in multiple sizes. AURA bronze sconce also exists in outdoor use.

Technical Specifications

Dimensions	Diam. 19 cm (7.4 in) × Depth 8 cm (3,1 in)	
Materials	bronze / alabaster	
Weight	3 kg / 6.6 lbs	
Lamping	Integrated AC LED module - 8-10W - 800 lm - 2700 K - dimmable	
Voltage	EU: 220-240 V	US: 120 V
Certifications	CE	ETL US
Protection	IP44 standard IP65 optional	Dry location
Flush-mounted electrical box	N/A	
Lead time	12 - 14 weeks	




8 cm
3,1 in



19 cm
7,4 in



Finishes / cast aluminium



Cast aluminium

Finishes / alabaster



The images above show the standard variations.

GARDE

AURA ALUMINIUM 18 SCONCE


A family of sconces composed of a cast aluminium shell and an alabaster disk. Can also be used as a flush mount. Available in multiple sizes. AURA aluminium sconce also exists in outdoor use.

Technical Specifications

Dimensions	Diam. 19 cm (7.4 in) × Depth 8 cm (3,1 in)	
Materials	cast aluminium / alabaster	
Weight	1.5 kg / 3.3 lbs	
Lamping	Integrated AC LED module - 8–10W - 800 lm - 2700 K - dimmable	
Voltage	EU: 220–240 V	US: 120 V
Certifications	CE	ETL US
Protection	IP44 standard IP65 optional	Dry location
Flush-mounted electrical box	N/A	
Lead time	12 - 14 weeks	




8 cm
3,1 in



19 cm
7,4 in




Finishes / bronze



Black patinated bronze




Brown patinated bronze



Gold patinated bronze

Finishes / alabaster



The images above show the standard variations.


GARDE

AURA BRONZE 25 SCONCE


A family of sconces composed of a sand-cast bronze shell and an alabaster disk. Can also be used as a flush mount. Available in multiple sizes. AURA bronze sconce also exists in outdoor use.

Technical Specifications

Dimensions	Diam. 26 cm (10.1 in) × Depth 10 cm (3.9 in)	
Materials	bronze / alabaster	
Weight	5 kg / 11 lbs	
Lamping	Integrated AC LED module - 8–10W - 800 lm - 2700 K - dimmable	
Voltage	EU: 220–240 V	US: 120 V
Certifications	CE	ETL US
Protection	IP44 standard IP65 optional	Dry location
Flush-mounted electrical box	N/A	
Lead time	12 - 14 weeks	




10 cm
3,9 in



26 cm
10,1 in



Finishes / cast aluminium



Cast aluminium

Finishes / alabaster



The images above show the standard variations.


GARDE

AURA ALUMINIUM 25 SCONCE


A family of sconces composed of a cast aluminium shell and an alabaster disk. Can also be used as a flush mount. Available in multiple sizes. AURA aluminium sconce also exists in outdoor use.

Technical Specifications

Dimensions	Diam. 26 cm (10.1 in) × Depth 10 cm (3.9 in)	
Materials	cast aluminium / alabaster	
Weight	2.5 kg / 5.5 lbs	
Lamping	Integrated AC LED module - 8-10W - 800 lm - 2700 K - dimmable	
Voltage	EU: 220-240 V	US: 120 V
Certifications	CE	ETL US
Protection	IP44 standard IP65 optional	Dry location
Flush-mounted electrical box	N/A	
Lead time	12 - 14 weeks	



10 cm
3,9 in



26 cm
10,1 in



Finishes / plaster



White plaster

Finishes / alabaster



The images above show the standard variations.


GARDE

AURA PLASTER 25 SCONCE


A family of sconces composed of a plaster shell and an alabaster disk. Can also be used as a flush mount. Available in multiple sizes.

Technical Specifications

Dimensions	Diam. 26 cm (10.1 in) × Depth 10 cm (3.9 in)	
Materials	plaster / alabaster	
Weight	1.3 kg / 2.9 lbs	
Lamping	Integrated AC LED module - 8-10W - 800 lm - 2700 K - dimmable	
Voltage	EU: 220-240 V	US: 120 V
Certifications	CE	UL Recognized components
Protection	IP44 standard IP65 optional	Dry location
Flush-mounted electrical box	N/A	
Lead time	12 - 14 weeks	



10 cm
3,9 in



26 cm
10,1 in