Maehwa Chandelier Cascade 39

MECHCD39



Materials

Transparent, translucent or blushed handblown borosilicate glass, handmade finish electroplated brass.

Weight incl. canopy

~29 lbs

Power Input

110-120V 50-60Hz

Light Source (included)

39 Proprietary Maehwa LEDs. 38 W, 4680 lm, 2700K warm white. CRI>95.Energy label A.

Modules:

1 x MEPEV13


1 x MEPEV09C

1 x MEPEV17




CONFIGURATION

STEP 1 - CHOOSE YOUR METAL FINISH



SIZE (UNIT: IN)



STEP 2 - CHOOSE YOUR GLASS COLOUR COMBINATION



TRANSPARENT







PALE PINK MIX*

blushed pale pink (21x) + translucent (18x)







SMOKEY GREY MIX*

blushed smokey grey (21x) + translucent (18x)

^{*}For a custom mix please contact the studio.

Steel Wire and Flex Cable Suspension, adjustable on site. Available options:

157" 393"

STEP 4 - CHOOSE YOUR CANOPY AND DRIVER

CANOPY + DRIVER

+ Single canopy with built-in phasecut driver. Recommended.



WHITE RAL 9016

PHASECUT

MATCHING FINISH



*Custom Canopy Colour (RAL Classic) available on request


+ Single canopy with built-in driver and alternative dimmable standards, if required by electrician.



WHITE RAL 9016

1-10 VOLT

MATCHING FINISH



Brass Finish

Brushed Brass

Brass hand finished with horizontal brushing. Protected with a semi-gloss transparent coating.

Brushed Bronze

Brass with accelerated aging to become a bronze finish. Hand finished with horizontal brushing. Protected with a semi-matt transparent coating.

Blackened Brass

Brass with accelerated aging to become an extra dark chocolate finish. Hand finished with horizontal brushing. Protected with a semi-matt transparent coating.

Brushed Nickel

Electroplated nickel over Brass with horizontal brushing.
Protected with a semi-gloss transparent coating.

Polished Nickel

Electroplated Nickel over polished brass. Protected with a semi-gloss transparent coating.











Custom Finish

Our products can be customized with most metal finishes, please check with our design advisors if you have any particular requirement.

Please advise if our products are to be installed close to air conditioning vents or in windy or salty air conditions.